What are rootkits	What type of subroutine can return data to the main program	What is the 8-bit binary representation of the decimal number 79
What is the ASCII character code method in string manipulation	What is an overflow error in binary addition	How does magnetic storage work

CSUK
© computerscienceuk.com | csuk.io

CSUK:Teacher
teacher.computerscienceuk.com | csukteacher.com

CSUK:ReviseCS
revisecs.computerscienceuk.com | revisecs.com

What are rootkits

- "A type of malware that provides unauthorized access to a computer system and can hide its presence and activity from users and security programs."

What type of subroutine can return data to the main program

A function.

What is the 8-bit binary representation of the decimal number 79

The 8-bit binary representation of the decimal number 79 is 01001111.

What is the ASCII character code method in string manipulation

The ASCII character code method in string manipulation returns the numeric code of a character in the ASCII character set.

What is an overflow error in binary addition

An overflow error occurs when the answer of binary addition is too large to be stored in a byte.

How does magnetic storage work

Answer: Magnetic storage uses magnetisation patterns to store data (tape/hard disk).

CSUK
© computerscienceuk.com | csuk.io

CSUK:Teacher
teacher.computerscienceuk.com | csukteacher.com

CSUK:ReviseCS
revisecs.computerscienceuk.com | revisecs.com